QuickSpecs

Overview

1.	Pen Tip	
2.	Pen Button	
3.	Pen Barrel	
4.	Pen Tether Eyelet	
5.	Battery Bay	
6.	Power Switch	
7.	Mobile Keyboard (attached)	

8.	AC Adapter Light
9.	Battery Light
10.	Wireless LAN/Bluetooth Activity Light
11.	Tablet PC Input Panel Launch
12.	Journal Launch Button
13.	Rotate Button

Front View

Right View

1.	Integrated Antenna
2.	Power Switch
3.	Power/Standby Light
4.	Display Toggle (F4) Button
5.	Windows Security Button (CTRL+ALT+DEL)
6.	Jog Dial

7.	Speaker (1 of 2)
8.	Microphone Jack
9.	Headset Jack
10.	Audio-out Jack
11.	Speaker (1 of 2)
12.	Microphone

Overview

Left View   **Back View**

1.	AC Power Connector	
2.	Integrated IR	
3.	External Monitor Connector	
4.	RJ-45 Network Jack	
5.	RJ-11 Telephone Jack	
6.	External Multibay Connector (USB 2.0)	

7.	USB 2.0 Connector
8.	Secure Digital (SD) Slot
9.	PC Card Slot
10.	Keyboard Connector
11.	Antenna (not visible from outside of tablet PC)
12.	Integrated Bluetooth

What's New

- Fast, Ultra Low Voltage Intel® Pentium® M 1.0GHz and Ultra Low Voltage Mobile Intel Celeron 800MHz processors
- Intel 855PM Chipset with better graphics from NVIDIA – GeForce 4 Go 420 32MB (4X AGP)
- More and faster system memory with 333MHz DDR on select models, up to 2GB max
- More storage available ranging from 30GB to 60GB hard drive
- Improved wireless performance and more choices for the integrated Type III MiniPCI WLAN
- Integrated Bluetooth on select models
- Dedicated Secure Digital (SD) slot for removable media
- Integrated IR
- Battery-free, pressure sensitive pen for the ultimate writing experience (application must support pressure sensitivity)
- Additional HP Security Lock Slot

At A Glance

- Microsoft® Windows® XP Tablet PC Edition
- Award winning design
- Durable magnesium casing
- Weighs 3.1 lb/1.4kg (with keyboard 4.0lb/1.8kg)
- Approximately .8 in/2.0 cm thin
- 10.4-inch XGA TFT display with sparkle-free glass
- Starting with 256MB or 512MB SDRAM upgradeable to 2GB
- Integrated mini PCI 56K V.90/V.92 modem plus 10/100 NIC
- Intel Pro/Wireless 2100 802.11b or HP W500 802.11a/b/g WLAN (availability may vary by region)

What's Special

- Flexible design with great performance!
- Ultra-light weight and portable
- Warm swap battery support
- Innovative keyboard attachment
- Docking with or without keyboard
- Easy transitions with multi-monitor docking profiles
- Magnesium alloy case and high quality digital pen with tether

QuickSpecs

Standard Features

Processor and Chipset	Ultra low Voltage Intel™ Pentium-M 1.0GHz processor with 400MHz Front Side Bus and 1MB cache	
	Ultra low Voltage Mobile Intel Celeron 800MHz processor with 400MHz Front Side Bus and 512KB cache	
	Intel 855PM chipset	

Display	Internal	10.4-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
		NOTE: All products have at least 100 degree wide viewing angle. Pentium-M SKUs available with 160 degree viewing angle.
	External	Up to 32-bit per pixel color depth
		Supports 640 x 480, 800 x 600, 1024 x 768, 1280 x 768, 1280 x 1024, or 1600 x 1200 resolutions up to 100-Hz refresh rate, dependent upon monitor capability, and resolution and color depth settings

Memory	Standard 512MB (333MHz) SDRAM on select models with Pentium-M processor
	Standard 256MB (266MHz) SDRAM on select models with Celeron processor
	One open user configurable memory slot on models with standard 256MB and 512MB, Maximum 2GB (333-MHz) SDRAM
	NOTE: Due to the non-industry standard nature of some third-party memory modules, we strongly recommend using only HP branded memory modules to ensure compatibility.

Graphics	NVIDIA GeForce 4 Go 420 with 32MB (4X APG)

Audio	16-bit stereo sound
	2 Stereo Speakers
	Headphone out, microphone jack, and headset jack

Communications	Integrated Type III MiniPCI WLAN adapter (Intel Pro/Wireless 2100 802.11b or HP W500 802.11a/b/g on select models)
	Internal MDC 56K (V.90/V.92) modem
	Internal 10/100 NIC
	Integrated Bluetooth (on select models)
	NOTE: Designed only to allow faster downloads from (V.90/V.92) compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions.
	NOTE: Communication availability is subject to country regulatory approval.

Command Controls Buttons	The tablet PC comes with Command Control Buttons designed to increase customer productivity by providing one-touch access to rotate screen, favorite Internet destinations, files, or applications.
	• 3 programmable pen activated buttons (on top front panel)
	• 3 programmable side buttons (Qmenu, Esc, and Tab commands)
	• 2 additional specific function buttons (Windows security (Ctrl+Alt+Del) and Display toggle)

Keyboard	95% of full-size 101-key compatible keyboard with isolated, inverted-T cursor control keys, and right-control key
	NOTE: A USB Keyboard is required to unbundle software and edit BIOS settings and may be required to install software.

Pointing Device	Battery-free digital pen with tether (one-year warranty)
	Detachable keyboard with pointstick
	NOTE: Handwriting recognition software is available in Microsoft Windows XP Tablet PC Edition.

QuickSpecs

HP Compaq Tablet PC TC1100

Standard Features

PC Card Slots	One Type II PC Card Slot that supports both 32-bit CardBus and 16-bit PCMCIA Cards

Removable Media	One Secured Digital (SD) slot

Storage   Internal Hard Drive   30GB, 40GB (4200 rpm) or 60GB (5400 rpm) SMART Hard drives

NOTE: External MultiBay or Tablet PC Docking Station required for MultiBay drives.

Multimedia   Integrated 16-bit Sound Blaster Pro-compatible stereo audio
2 Integrated stereo speakers and microphone
Stereo Headphone-out
Mono Headphone-out/Microphone in
Software MPEG1 support

- DVD movie playback software available with
  - DVD-ROM Drive with DVD movie playback
  - DVD/CD-RW Combo Drive
  - DVD+RW Drive

NOTE: Voice recognition software available in Microsoft Windows XP Tablet PC Edition. An external boom microphone is recommended for voice recognition.

Interfaces

PC Card Slot	1, Type II
Secured Digital (SD) Slot	1 removable media (not SDIO)
External Monitor/Projector	1 Analog VGA
Stereo Headphone	1, 3.5 mm stereo headphone jack
Mono Headphone/ Microphone	1, 2.5 mm headset jack
Stereo Microphone in	1, 3.5 mm microphone jack
Modem	1 RJ-11
NIC	1 RJ-45
USB 2.0 Port	2, 1 with support for External MultiBay
LED Status Indicators	3 (Power connection, battery charge, and wireless active)
AC Power	1
Fast Infra-red (VFIR)	1

Security   Setup Password with pen support
Power-On Password with pen support
DriveLock – requires password to access hard drive
Enabled by PC Card options
BIOS WLAN lock – prevents the replacement with unauthorized WLAN cards
2 HP Security locks – physically secure unit while in tablet, docking, or notebook modes

Operating System   Pre-installed   Microsoft Windows XP Tablet PC Edition

invent

footer

DA - 11755   Worldwide — Version 5 — March 1, 2004   Page 4

Standard Features

Software	Pre-installed Software	HP Mobile Printing for Notebooks HP Help and Support (XP Only) Safety and Comfort Guide Adobe Acrobat® Reader v. 5.10 Microsoft Reader v. 2.5 Zinio Reader v.1.4 Sun Java 1.4 Windows Media Player 9 for XP HP Tablet PC Tour *Intervideo WinDVD Playback Software v. 4* (Pre-loaded)
	Recommended software/ services	Availability of recommended software applications or services may vary by region and may require additional purchase and/or subscription FranklinCovey TabletPlanner v. 2.0 (30 day trial period) MindJet MindManager 2002 for Tablet PC (21 day trial period) Corel Grafigo v. 1.0 (promotional free download) Zinio (see Digital Magazine icon on Tablet PC desktop for more information) ScanSoft Omniform Filler 5.1 and Dragon Naturally Speaking Standard Edition 7.1 (available as a special configuration)
	Additional software available through the web	HP Client Manager Software HP ProtectTools Embedded Security Manager HP ProtectTools Smart Card Security Manager QuickLook for the HP Tablet PC TC1100 series

*NOTE: Software is loaded on the hard drive and must be installed by running the Software Setup utility

---

System Recovery

Each unit is shipped with a recovery CD kit containing Operating System Recovery and Driver/Application Recovery CDs. These CDs allow users to either recover or repair the tablet's operating system and select drivers without losing personal data. The Operating System CD also provides the option of reinstalling the operating system software provided with the tablet.

Power Supply

65W External AC Adapter

Battery

40W/Hr internal main rechargeable Lithium-Ion battery (one-year warranty)
Bridge battery - Allows user to swap main battery with the system in standby mode.

Battery Re-Charge Time	System in OFF mode or Standby	3 hours
	System ON (depending on system power consumption)	3-5 hours

Power Conservation

Instant-on via Standby
Hibernation
ACPI compliant

MultiBay Devices
(with optional External MultiBay or Docking Station)

Under Microsoft Windows XP Tablet PC Edition, MultiBay devices may be hot swapped. Writeable drives should only be swapped with power off. The Common MultiBay devices are compatible across TC1000 and TC1100 tablets, and multiple business notebook platforms enabling a lower total cost of ownership.


Docking

The HP Tablet PC Docking Station provides simple and convenient port management MultiBay drives. Features include NIC pass through, Four USB 2.0 including 1 Powered External USB MultiBay connector, VGA, line in /line out, and MutliBay slot, The docking solutions is compatible across TC1000 and TC1100 tablets enabling a lower total cost of ownership.

QuickSpecs

Standard Features

Service and Support	HP Services includes a One-Year or Three-year, Worldwide Limited Warranty, pick-up or carry-in (in select countries) and toll-free 7 x 24 hardware technical phone support.
	NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details.

The Etymology of a Model name:

```
•SUB-BRAND/FAMILY ( CTC1100=Compaq TC1100 )
  •GRAPHICS ( Q=Discrete 32MB )
    •PROCESSOR TYPE ( P=Pentium; C=Celeron )
      •PROCESSOR SPEED ( 100=1.0GHz; 800=800MHz )
        • DISPLAY SIZE ( X=XGA ; 0=10.4 inch )
          •HARD DRIVE ( 40=40GB ; 30=30GB )
            • OPTICAL DRIVE ( N=None )
              • COMM DEVICE ( C=Combo Modem + FE NIC )
                •WIRELESS ( i=802.11b + Bluetooth )
                  •MEMORY ( 51=512MB ; 25=256MB )
                    •OPERATING SYSTEM ( T=XP Tablet )

CTC1100 Q P 100 X0 40 N C i 51 T
```

Models

Commercial - Regional Value SKU for Americas, EMEA, APD			
CPU	Ultra-Low Voltage Mobile Intel Celeron 800MHz with 400MHz Front Side Bus and 512KB cache		
Display	10.4-inch color TFT XGA with 1024 x 768 resolution (100 degree viewing angle)		
Memory	Standard	256MB 266MHz DDR SDRAM with one open slot	
	Maximum	1GB 333MHz DDR SDRAM in each slot (2GB max)	
Hard Drive	30GB		
Discrete Video Memory	NVIDIA - GeForce 4 Go 420 32MB (4X AGP)		
Communications	Internal MDC 56K (V.90/V.92) modem, NIC 10/100, Intel Pro/Wireless WLAN 802.11b, Bluetooth		
Input Device	Tablet PC Pen with tether, HP Tablet PC Keyboard with Pointstick		
Operating System	Microsoft Windows XP Tablet PC Edition		
Battery	6-cell Lithium-Ion		

Commercial - "Centrino" Semi-Global SKU for Americas, EMEA, APD			
CPU	Ultra-Low Voltage Intel Pentium-M 1.0GB with 400MHz Front Side Bus and 1MB cache "Centrino"		
Display	10.4-inch color TFT XGA with 1024 x 768 resolution (160 degree viewing angle)		
Memory	Standard	512MB 333-MHz DDR SDRAM with one open slot	
	Maximum	1GB 333-MHz DDR SDRAM in each slot (2GB max)	
Hard Drive	40GB		
Discrete Video Memory	NVIDIA - GeForce 4 Go 420 32MB (4X AGP)		
Communications	Internal MDC 56K (V.90/V.92) modem, NIC 10/100, Intel Pro/Wireless WLAN 802.11b, Bluetooth		
Input Device	Tablet PC Pen with tether, HP Tablet PC Keyboard with Pointstick		
Operating System	Microsoft Windows XP Tablet PC Edition		
Battery	6-cell Lithium-Ion		

Options

Memory		
	256MB 333MHz RAM Memory Upgrade	DC389B
	512MB 333MHz RAM Memory Upgrade	DC390B
	1GB 333MHz RAM Memory Upgrade	DC890B

NOTE: Due to the non-industry standard nature of some third-party memory modules, we strongly recommend using only HP branded memory modules to ensure compatibility.

MultiBay Devices		
	16X DVD+RW/CD-RW Drive	DG189A
	24X Combo DVD/CD-RW Drive	DC364A
	24X CD-RW Drive	DC921A
	8X DVD Drive	DC352A
	24X Max CD-ROM Drive	DC351A
	MultiBay Diskette Drive	DC362A

NOTE: MultiBay devices may only be used in External MultiBay or Docking Station MultiBay.

MultiBay Storage		
	USB MultiBay Diskette Drive	DC361A
	30GB MultiBay Hard Disk Drive (4200 rpm)	212791-B25
	40GB MultiBay Hard Disk Drive (4200 rpm)	DC365A
	60GB MultiBay Hard Disk Drive (5400 rpm)	DC894A

NOTE: MultiBay hard drive options may only be used in External MultiBay or Docking Station MultiBay.

Other Storage Devices		
	IBM 1-GB Microdrive (PC card Device)	217390-B25
	16MB USB Disk-on-Key	DC192A
	64MB USB Disk-on-Key	DC191A
	128MB USB Disk-on-Key	DC190A

Other Options		
	1394 PC Card	DD797A

Expansion Bases		
	Tablet PC Docking Station	DC911A#xxx
	External MultiBay	DC373A#B13

Power		
	Tablet PC Lithium-Ion battery pack (internal)	DC907A

Common Power Solutions		
	Battery Charger	DC887A#XXX
	65W AC Adapter	DC359A#XXX
	65W Auto AC Adapter	DC360A
	90W AC Adapter	DC895A#XXX
	90 W Auto Adapter	DC303A
	90W Aircraft Cables	DC899A
	Valence Battery	DC899A

QuickSpecs

Options

Input Devices		
	Tablet PC Mobile Keyboard	DC910A#XXX
	Tablet PC Pen with tether	DG937A
	Tablet PC Pen with eraser	DM685A
	External Enhanced III Keyboard (carbon)	DC852A#XXX
	USB/PS2 (2)Button Mouse (carbon)	DC369A
	HP Travel Mouse	F4815A
	External 10-Key Numeric Keypad (carbon)	DC854A
	SmartCard Keyboard USB	267147-008

Security		
	Biometric ID Device PC Card	DC859A
	Security Cable Lock	DC368A
	PC Guardian Security Cable Lock	261680-B21
	DEFCON Security Lock	201708-001
	DEFCON Security System	158638-001

Useful Accessories		
	Tablet PC Executive Slim-line Portfolio	DC912A
	Tablet PC Executive Workstation Portfolio	DC909A

Carrying Cases		
	HP Entry Value	DC914A
	Top Load Nylon	DC915A
	Executive Nylon	DC916A
	Executive Leather	DC917A

Technical Specifications

System Unit	Dimensions (H x W x D)	10.4-inch TFT panel display	10.8 x 8.5 x 0.8 in (27.4 x 21.6 x 2.0 cm)
	Weight	Approximate	3.1 lb (1.4 kg) Tablet PC only
			4 lb (1.8 kg) Tablet PC with keyboard
	Stand-Alone Power Requirements	Nominal Operating Voltage	14.8 VDC
		Peak Operating Power	40W
	Temperature	Operating	50° to 95° F (10° to 35° C)
		Non-operating	-4° to 140° F (-20° to 60° C)
	Relative Humidity	Operating	10% to 90% relative humidity, non-condensing
		Non-operating	5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
	Shock	Operating	10 G, 11 ms, half-sine
		Non-operating	60 G, 11 ms, half-sine
	Vibration	Operating	0.5 G, 10 to 500 Hz, 0.5 Oct/Min sweep rate
		Non-operating	1.0 G, 10 to 500 Hz, 0.5 Oct/Min sweep rate
	Maximum Altitude (unpressurized)	Operating	0 to 10,000 ft (3,048 m), (14.7 to 10.1 psia)
		Non-operating	0 to 30,000 ft (9,144 m), (14.7 to 4.4 psia)

10.4-Inch Color TFT XGA Display	Dimensions (H x W)	9.29 x 6.82 in (23.6 x 17.3 cm)	
	Diagonal Size	10.4 in (26.41 cm)	
	Mounting	Internal Panel Supports, Flange Mounted	
	Number of Colors	Up to 16.8M	
	Contrast Ratio	150:1	
	Brightness	140 nits typical	
	Pixel Resolution	Pitch	0.264 x 0.264 mm
		Format	1024 x 768
		Configuration	RGB stripe
	Backlight	Edge Lit	
	Character Display	80 x 25	
	Wide Viewing Angle	100 degrees with Celeron SKUs	
		160 degrees with Pentium-M SKUs	

Memory (optional)	Slot 1 (Factory and Service configurable only)	256MB 266MHz DDR	Standard with Celeron SKUs (may also use 333MHz)
		256MB 333MHz DDR	
		512MB 333MHz DDR	Standard with Pentium SKUs
		1GB 333MHz DDR	
	Slot 2 (open)	256MB 333MHz DDR	
		512MB 333MHz DDR	
		1GB 333MHz DDR	

External AC Adapter	Weight	0.62 lb (0.28 kg)	
	Power Supply (Input)	Operating Voltage	90 to 260 VAC RMS
		Operating Current	1.7 A RMS
		Operating Frequency Range	47 to 63 Hz AC

QuickSpecs

Technical Specifications

Internal Lithium-Ion Battery Pack	Weight	0.65 lb (0.30 kg)	
	Cells	6-cell Lithium-Ion	
	Energy	Voltage	11.1 V
		Amp-hour capacity	3.6Ah
		Watt-hour capacity	40Wh
	Temperature	Operating (Charging)	32° to 104° F (0° to 40° C)
		Operating (Discharging)	14° to 122° F (-10° to 50° C)
		Non-operating	-4° to 140° F (-20° to 60° C)
	Battery Re-Charge Time	System in OFF mode or Standby	3 hours
		System ON (depending of system power consumption)	3 to 5 hours

Tablet PC Pen(s)	Pen with tether (standard)	Dimensions (Length)	5.1 in (130.1 mm)
		Weight	0.66 oz (18.7 g)
	Pen with eraser (optional)	Dimensions (Length)	5.1 in (130.1 mm)
		Weight	0.66 oz (18.7 g)

MultiBay DVD+RW/CD-RW Drive (optional)	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.55 lb (0.25 kg)
	Center Hole Diameter	15 mm	
	Disk Diameter	12 cm/8 cm	
	Disk Thickness	1.2 mm	
	Track Pitch	0.74 μm	
	Access Times (typical reads, including settling)	Random CD	< 175 ms
		Full-Stroke CD	< 285 ms
	Audio Output Level	Line-out	0.7 Vrms
	Cache Buffer	128 KB/s (minimum)	
	Data Transfer Rate (typical, including settling)	DVD+R (2X max write)	2700 KB/s
		DVD+RW (2X max write)	2700 KB/s
		CD-R (16X max write)	2400 KB/s (150 KB/s at 1X CD rate)
		CD-RW (8X max write)	1200 KB/s (150 KB/s at 1X CD rate)
		CD-ROM (24X max read)	3600 KB/s (150 KB/s at 1X CD rate)
		DVD (8X max read)	10,800 KB/s (1352 KB/s at 1X DVD rate)
		Normal PIO Mode 4 (single burst)	16.6 MB/s
	Start-up Time	< 15 seconds	
	Stop Time	< 6 seconds	

QuickSpecs

Technical Specifications

MultiBay CD-RW Drive (optional)	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.74 lb (0.34 kg)
	Center Hole Diameter	0.59 in (1.5 cm)	
	Disk Diameter	12 cm/8 cm	
	Disk Thickness	0.047 in (1.2 mm)	
	Track Pitch	0.74 μm	
	Access Times (typical reads, including settling)	Random	< 150 ms
		Full-Stroke	< 225 ms
	Audio Output Level	Line-out	0.7 Vrms
	Cache Buffer	128 KB/s (minimum)	
	Data Transfer Rate (typical, including settling)	Sustained (16X)	150 KB/s
		Sustained 4X CD-RW	5,520 KB/s
		Normal PIO Mode 4 (single burst)	16.6 MB/s
	Start-up Time	< 15 seconds	
	Stop Time	< 6 seconds	

MultiBay DVD-ROM Drive (optional)	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.66 lb (0.3 kg)
	Center Hole Diameter	0.59 in (1.5 cm)	
	Disk Diameter	12 cm/8 cm	
	Disk Thickness	0.43 in (1.09 cm)	
	Track Pitch	0.74 μm	
	Access Times (typical reads, including settling)	Random (typical)	< 180 ms DVD Media
		Full-Stroke (typical)	< 300 ms DVD Media
		Random (typical)	< 120 ms CD Media
		Full-Stroke (typical)	< 200 ms CD Media
	Cache Buffer	512 KB/s (minimum)	
	Data Transfer Rate (typical, including settling)	Max 24X CD	3600 KB/s (150 KB/s at 1X CD rate)
		Max 8X DVD	10,800 KB/s (1352 KB/s at 1X DVD rate)
		Normal PIO Mode 4 (single burst)	16.6 MB/s
	Start-up Time	< 12 seconds	
	Stop Time	< 3 seconds	

QuickSpecs

Technical Specifications

MultiBay 24X CD-ROM Drive (optional)	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.50 lb (0.23 kg)
	Applicable Disk	CD-ROM (Mode 1, 2 and 3), CD-XA ready (Mode 2, Form 1 and 2), CD-I ready (Mode 2, Form 1 and 2), CD-R (read only), CD Plus, Photo CD (Single and Multi-session), CD-Extra, Video CD, CD-WO (fixed packets only), CD-Bridge	
	Center Hole Diameter	0.59 in (15 mm)	
	Disk Diameter	12 cm, 8 cm	
	Disk Thickness	0.047 in (0.12 cm)	
	Track Pitch	1.6 μm	
	Access Times (typical reads, including settling)	Random	< 150 ms
		Full-Stroke	< 300 ms
	Audio Output Level	Line-out	0.7 Vrms
	Cache Buffer	128 KB	
	Data Transfer Rate (typical, including settling)	Sustained (16X)	150 KB/s (sustained 1X)
		Variable	1500 to 3600 KB/s (10X to 24X)
		Normal PIO Mode 4 (single burst)	16.66 MB/s
	Start-up Time	< 8 seconds	
	Stop Time	< 4 seconds	

Technical Specifications

Internal MDC 56K (V.90/V.92) (Modem Specifications)	Modem Device Driver Name	
	Data Mode Capabilities	V.92/ V.90 (a-law, mu-law) V.8bis V.80 V.44, V42.bis, MNP5 (Compression) V.42 (LAPM, MNP2-4) (Error Correction) V.34 (file date: 10/96)
		Optional symbol rates: 2800, 3429 Asymmetric Symbol rates
		Synchronous primary channel data signaling rates: 33600, 31200 Automatic rate re-negotiation V.32bis V.32 V.23 V.22bis V.22 V.21 Bell 212A Bell 103J
	Fax Mode Capabilities	TIA-578-S (Class 1) T.30, T.4 (Group 3) V.17 V.29 V.27ter V.21 Channel 2
	Command Set	V.250 (Partial) TIA-602 Identification: GMI, GMM, GMR Port control: IPR, ICF, IFC, Iirr Modulation: MS, MR, MA Error control: ES, ER, EB, ESR, ETBM Data compression: DS, DR V.251
	Power Consumption	Transfer mode: < 200 mA, maximum Standby mode: 5 mA, nominal

Integrated 10/100 NIC	**Ethernet Features**	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) Auto-Negotiation (Automatic Speed and Duplex Selection) HP Auto-MDIX Full Duplex and Half Duplex operation at 10 and 100 Mbit/s IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)
	Power Management	ACPI 1.1 compliant -- multiple power modes Situation-sensitive features reduce power consumption
	Manageability	PXE 2.0 Remote Boot Statistics Gathering (RMON, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite
	NIC Device Driver Name	Broadcom 440x 10/100 Integrated Controller
	Drivers Available	Microsoft Windows XP, Windows 2000 DOS NDIS2 and ODI

Technical Specifications

HP W500 802.11a/b/g WLAN (availability may vary by region)	**Wireless LAN Standards**	IEEE 802 Part 11a (802.11a) IEEE 802. Part 11b (802.11b) IEEE 802. Part 11g (802.11g)	
	Interoperability	Wi-Fi certified	
	Frequency Band	2.4 and 5 GHz	
	Data Rates	802.11a; 6,9,12,18,24,36,48,54 Mbps 802.11b; 1,2,5.5,11 Mbps 802.11g; 6,9,12,18,24,36,48,54 Mbps	
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM	
	Security	64 and 128 bit WEP encryption Support for WiFi Protected Access (WPA) including TKIP, MIC Hardware-accelerated support for the Advanced Encryption Standard (AES; 256-bit encryption) Support for 802.1x authentication types: EAP-TLS, LEAP (Cisco), PEAP (Microsoft implementation) Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program).	
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.	
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK	
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)	
	Roaming	IEEE 802.11 compliant roaming between 802.11a and 802.11b/g access points	
	Output Power	802.11b: 17 dBM (typical) 802.11a/g: 15 dBM (typical)	
	Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Sleep mode: 20 mW (max)	
	Power Management	ACPI compliant power management 802.11 Compliant Power Saving Mode Power Saving Mode selectable through the configuration utility	
	Receiver Sensitivity*	54 Mbps: -70 dBm to 1 Mbps: -90 dbm	
	Antenna type	High efficiency dual band antenna with polarization diversity, mounted in the display enclosure	
	Range	802.11a - Typical	500 feet - Outdoors Open Area 150 feet - Indoor, Office-environment
		802.11 b - Typical	1200 feet - Outdoor Open Area 300 feet - Indoor, Office environment
		802.11 g - Typical	1000 feet - Outdoor Open Area 200 feet - Indoor, Office environment
	Form Factor	MiniPCI Type IIIA	
	Weight	0.036 lb (16.5 gm)	
	Dimensions	0.19 x 2.00 x 2.35 in (4.8 x 50.95 x 59.75 mm)	
	Operating Voltage	3.3v	
	Temperature	Operating Non-operating	32° to 122° F (0° to 50° C) -14° to 158° F (-10 to 70° C)
	Humidity	Operating Non-operating	10 to 90% 5 to 95%
	Altitude	Operating Non-operating	0 to 15,000 ft (4,572 m) 0 to 40,000 ft (12,192 m)
	Configuration Utility	Choice of Configuration Utility:	

- Atheros Client Utility (required for Cisco Compatible Extensions support)
- Microsoft Windows XP Wireless Zero Configuration Utility

NOTE: may also be compatible with certain third party software supplicants

Technical Specifications

	LED Activity	LED Off - WLAN and Bluetooth Radio OFF; Solid Green LED - WLAN or Bluetooth Radio ON (please refer to your Tablet PC documentation to determine whether WLAN or Bluetooth is activated)

*Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation)

Intel Pro/Wireless 2100 802.11b WLAN	Wireless LAN Standards	IEEE 802. Part 11b (802.11b)	
	Interoperability	Wi-Fi certified	
	Frequency Band	2.4 GHz	
	Data Rates	802.11b; 1,2,5.5,11 Mbps	
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK	
	Security	64 and 128 bit WEP encryption Support for WiFi Protected Access (WPA) including TKIP, MIC Support for 802.1x authentication types: EAP-TLS, LEAP (Cisco), PEAP (Microsoft implementation) Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program).	
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.	
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK	
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)	
	Roaming	IEEE 802.11 compliant roaming between 802.11b access points	
	Output Power	16 dBM (typical)	
	Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Sleep mode: 200mW, nominal	
	Power Management	ACPI compliant power management 802.11 Compliant Power Saving Mode	
	Receiver Sensitivity*	11 Mbps: -82 dBm to 1 Mbps: -89 dBm	
	Antenna type	High efficiency dual band antenna with polarization diversity, mounted in the display enclosure	
	Range	802.11b - Typical	1200 feet - Outdoor Open Area 300 feet - Indoor, Office environment
	Form Factor	MiniPCI Type IIIB	
	Weight	0.026 lb (11.75 gm) (max)	
	Dimensions	0.20 x 1.75 x 2.34 in (4.9 x 44.6 x 59.8 mm)	
	Operating Voltage	3.3v	
	Temperature	Operating Non-operating	32° to 158° F (0° to 70° C) -40° to 176° F (-40° to 80° C)
	Humidity	Operating Non-operating	0 to 90% (non-condensing) 5 to 95% (non-condensing)
	Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)

Technical Specifications

Configuration Utility	Choice of Configuration Utility:	

- Intel ProSet (required for Cisco Compatible Extensions support)
- Microsoft Windows XP Wireless Zero Configuration Utility

NOTE: may also be compatible with certain third party software supplicants

LED Activity   LED Off - Radio OFF; Solid LED - Radio ON

*Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation)

Bluetooth by HP	**Form Factor**	Integrated USB module	
	Bluetooth	1.1 Compliant	
	Dimensions	26 x 14 x 5.7 mm	
	Temperature	Operating	-4° to 158° F (-20° to 70° C)
		Non-operating	-40 to 176 F (-40° to 80° C)
	Humidity	10 to 90% operating	
		5 to 95% non operating	
	Altitude	Operating	15,000 ft (4572 m)
		Non-operating	40,000 ft (12,192 m)
	Plug and Play	USB 1.1 compliant	
		Microsoft Windows Plug and Play compliant	
	Frequency Band	2402 to 2480 MHz	
	Number of Available Channels	79 (1 MHz) available channels	
	Data Rates and throughput	1 Mbps	
		Synchronous Connection Oriented links up to 3, 64 kbps, voice channels	
		Asynchronous Connection Less links 723.2 kbps/57.6 kbps asymmetric or 433.9 kbps symmetric	
	Antenna type	Internally integrated within module	
	Range	33 ft/10 m	
	Software Stack Supported	User may choose:	
		Microsoft User Interface (Profiles supported: HID, DUN, HCRP)	
		Widcomm User Interface (see profile support below)	
	Profile Support	General Access Profile	
		Service Discovery Application Profile	
		Serial Port Profile	
		Generic Object Exchange Profile	
		File Transfer Profile	
		Synchronization Profile	
		Dial-Up Networking Profile	
		LAN Access Profile	
		Object Push Profile	
		Hard Copy Cable Replacement Profile	
		Personal Area Networking Profile	
		Human Interface Device Profile	
	Usage Models	Service Discovery (determine what Bluetooth devices are within range and support authorization)	
		Synchronization: PDAs to PCs Portable to Desktop	
		File Transfer:	

Technical Specifications

	File and directory browsing and navigation on another Bluetooth device. File copying Object manipulation - including add, delete, create new folders etc. Wireless link to Corporate LAN using several Bluetooth devices sharing the same
	Access Point: Corporate email, network neighborhood, access to LAN applications, file transfer, ftp, Internet browsing, etc, using TCP/IP Wireless link to WAN thru cell phone Agnostic to WAN technology Send/receive SMS messages Wireless link to Printer Adhoc peer to peer networking (two computers) or Personal Area Networking (PAN) using NDIS (< 7 computers) Adhoc Bluetooth Pico-networking (point to multi-point) Object Push - Business card or appointment exchange **Human Interface Devices** Wirelessly interface to notebook with mouse, keyboard, etc **Printing** Wirelessly print to Bluetooth enabled printers
Transmit Power	-6dBm to 4 dBm (Bluetooth Class II)
Receive Sensitivity	Better than -80 dBM at 0.1 % raw bit error rate
Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves
Security	Full support of Bluetooth Security Provisions
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Points Required)
Power Requirement	Peak < 270 mW
Power Management	Microsoft Windows ACPI, and USB Bus Support Wireless EAB On/Off Software On/Off control Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
Protocols Supported	TCP/IP IPX/SPX UDP
LED Activity	Solid Green LED - Wireless Bluetooth or WLAN On LED Off - Wireless Bluetooth and WLAN Power Off (please refer to your Tablet PC documentation to determine whether WLAN or Bluetooth is activated)
Certifications	All necessary regulatory approvals for countries we support including FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark